


## Item # DC 60, DC Series Chemically Cleanable Desuperheaters (5 to 100 tons)



**Call dii**

**Heat recovery unit for domestic hot water from air conditioning and refrigeration systems up to 100 tons**

DC Series Chemically Cleanable Commercial Desuperheaters recycle rejected heat from your air conditioning or refrigeration system and use it to heat water or other fluids. At the same time, desuperheating lowers refrigerant temperature and pressure, reducing energy input to the compressor. You save by reducing or eliminating the energy required for water heating while increasing the efficiency of the air conditioning/refrigeration system.

- Heats potable water up to 140 °F using waste heat
- Typical Payback Period of Two Years or Less
- Reduces A/C operating costs 5% to 10%
- Chemically Cleanable Counterflow Design
- Compact and Ready to Install
- Works with All Major Manufacturers' Systems

### Specifications

TR	60 tons	
Application	<ul style="list-style-type: none"> <li>• Domestic Hot Water Heating</li> <li>• Process Water Heating</li> <li>• Space Heating</li> <li>• Pool Heating</li> <li>• Hot Deck Reheat</li> <li>• Sub-Soil Heating</li> <li>• Restaurants</li> <li>• Hotels/Motels</li> <li>• Hospitals</li> <li>• Schools</li> <li>• Food Processing</li> <li>• Ice Rinks</li> <li>• Dormitories</li> </ul>	
# Circuits	1	
Cleanability	Chemical	
Refrig. Conn.	2-5/8" OD	



20 Leigh Drive,  
York, Pennsylvania 17406-8474



Website: [www.doucetteindustries.com](http://www.doucetteindustries.com)



Phone: 717-845-8746  
Toll-free: 800-445-7511  
Fax: 717-845-2864



Commercial/Industrial: [AdamM@doucetteindustries.com](mailto:AdamM@doucetteindustries.com)  
Residential/Light Commercial: [AdamM@doucetteindustries.com](mailto:AdamM@doucetteindustries.com)



Water Conn.	1-3/8" OD
Length	50-1/8 "
Width	12-3/4 "
Height	23-3/16 "
Weight	420 lbs

#### **Mechanical Specifications**

Optional Pump	Grundfos UPS15-55 SFC, Circulating Pump (\$1075.00)
Heat Exchanger	Chemically cleanable, vented double wall, U.L. listed, 450 psig shell side DWP (optional 600 psig), 300 psig tube side DWP
Cabinet	0.040" Aluminum Alloy, insulated, weather-resistant cabinet, with removable service panel. Bottom mounting rails provided as standard.





96318.dwg



CONNECTIONS:		TOLERANCES		DOUCETTE INDUSTRIES, INC.	
1.) REFRIGERANT SUPPLY	2-5/8"	DD	COPPER	SWEAT	
2.) WATER RETURN	1-3/8"	DD	COPPER	SWEAT	
3.) WATER SUPPLY	1-3/8"	DD	COPPER	SWEAT	
4.) REFRIGERANT RETURN	2-5/8"	DD	COPPER	SWEAT	

TOLERANCES		DOUCETTE INDUSTRIES, INC.	
DECIMAL	.125	SCALE	DRAWN BY: RLK
+			APP. BY: RJR
FRACTIONAL		TITLE	DC 60 (C)
+		DATE	12/17/15
		DRAWING NUMBER	96318
GAUGE	20	ALL DIMENSIONS	INCHES, UNLESS SPECIFIED

4.875 X 12.75 X 17.875;
-------------------------

44.875 X 12.75 X 17.875;

